

MIT OpenCourseWare
<http://ocw.mit.edu>

6.189 Multicore Programming Primer, January (IAP) 2007

Please use the following citation format:

Saman Amarasinghe and Rodric Rabbah, *6.189 Multicore Programming Primer, January (IAP) 2007*. (Massachusetts Institute of Technology: MIT OpenCourseWare). <http://ocw.mit.edu> (accessed MM DD, YYYY).
License: Creative Commons Attribution-Noncommercial-Share Alike.

Note: Please use the actual date you accessed this material in your citation.

For more information about citing these materials or our Terms of Use, visit:
<http://ocw.mit.edu/terms>

How to get X to work on the PS3 console

To start X on the PS3 console, log in then type `startx` on the command line. If you encounter an error:

```
(EE) Unable to locate/open config file
```

then you need to first run `xautoconfig` (as root) to create the config file `/etc/X11/xorg.conf`.

```
% login root
% Xautoconfig
Wrote /etc/X11/xorg.conf
```

Now try `startx` again and test that X is working properly by running `emacs`. If you encounter errors of the kind

```
Undefined color: "black"
```

then edit `/etc/X11/xorg.conf` and remove the `.txt` extension in `rgb.txt` that appears on this line

```
RgbPath "/usr/share/X11/rgb.txt"
```

or comment out the line to force the X server to use the compiled in path. Now restart X, and retest.